DERWENT ABSTRACT FOR: JP 2000-143891 (Asahi, Honda), published 26 May 2000:

ANSWER 1 OF 14 WPINDEX COPYRIGHT 2001 DERWENT INFORMATION LTD

ACCESSION NUMBER: 2000-426148 [37] WPINDEX

DOC. NO. CPI: C2000-129584

Thermoplastic resin composition for automobile radiator TITLE:

tank/secondary battery container. DERWENT CLASS:

A13 A17 A26 A85 A95 L03

PATENT ASSIGNEE(S): (ASAH) ASAHI KASEI KOGYO KK; (HOND) HONDA MOTOR CO LTD

COUNTRY COUNT: 1

PATENT INFORMATION:

PATENT NO KIND DATE WEEK LA PG ------JP 2000143891 A 20000526 (200037)* 9 <--

APPLICATION DETAILS:

PATENT NO KIND APPLICATION DATE -----JP 2000143891 A JP 1999-116108 19990423

PRIORITY APPLN. INFO: JP 1998-255708 19980909

AN 2000-426148 [37] WPINDEX AB JP2000143891 A UPAB: 20000807

NOVELTY - A thermoplastic resin composition contains: (a) a polyolefin-based resin, 95-5 percent by weight; (b) a polystyrene-based resin having mainly a syndiotactic structure, 5-95 percent by weight; and at least (c) a thermoplastic elastomer, 0.5-100 parts by weight; and (d) a polyphenylene ether resin, 0.5-100 parts by weight. The weight of (c) and (d) is based on 100 parts by weight of (a) and (b).

USE - The thermoplastic resin composition is used in an automobile radiator tank, a secondary battery container.

ADVANTAGE - The thermoplastic resin composition has superior solvent resistance, resistance to water vapor permeability, and impact strength resistance, and no decrease in mechanical strength after long-term service at high temperatures. Enhanced heat resistance, impact strength resistance, and rigidity are observed in glass fiber reinforcement. Dwg.0/1